

Tiger Lights Mojave Series Product Guide



SKU:	3511	3512	3513	3514 & 3515	3516	3517
TIGER LIGHTS #:	TLM8	TLM5	TLM4	TLM3 & TLM3-FM	TLM2X3	TLM2
LENS INCLUDED W/ LIGHT PURCHASE*:	- Clear Combo Lens - Clear Lens Cover - Amber Lens Cover	- Clear Combo Lens - Clear Lens Cover - Amber Lens Cover	- Clear Combo Lens - Clear Lens Cover - Amber Lens Cover	- Clear Combo Lens - Clear Flood Lens - Clear Spot Lens	- Clear Combo Lens - Clear Flood Lens - Clear Spot Lens	- Clear Wide Flood Lens - Clear Flood Lens - Clear Spot Lens
ADDITIONAL LENS* (SOLD SEPARATELY):	3518 TLM8-ALC - Amber Combo Lens - Replacement O-Ring	3519 TLM5-ALC - Amber Combo Lens - Replacement O-Ring	3520 TLM4-ALC - Amber Combo Lens - Replacement O-Ring	3521 TLM3-ALP - Amber Combo Lens - Amber Flood Lens - Amber Spot Lens - Replacement O-Ring	3522 TLM2X3-ALP - Amber Combo Lens - Amber Flood Lens - Amber Spot Lens - Replacement O-Ring	3523 TLM2-ALP - Amber Wide Flood Lens - Amber Flood Lens - Amber Spot Lens - Replacement O-Ring
BLACK GRAPHIC LENS COVER:	3524 TLM8-LC	3525 TLM5-LC	3526 TLM4-LC	3527 TLM3-LC (ONLY FOR TLM3)	N/A	N/A
REPLACEMENT O-RING* (SEAL):	3528 TLM8-OR	3529 TLM5-OR	3530 TLM4-OR	3531 TLM3-OR	3532 TLM2X3-OR	3533 TLM2-OR
LIGHT KITS:	3534 TLM8-KIT - 2 x 3511 (TLM8) - 2 x 3524 (TLM8-LC) - 1 x TLMWH3 (wiring harness)	3535 TLM5-KIT - 2 x 3512 (TLM5) - 2 x 3525 (TLM5-LC) - 1 x TLMWH3 (wiring harness)	3536 TLM4-KIT - 2 x 3513 (TLM4) - 2 x 3526 (TLM4-LC) - 1 x TLMWH3 (wiring harness)	3537 TLM3-KIT - 2 x 3514 (TLM3) - 1 x TLMWH2 (wiring harness) 3538 TLM3-FM-KIT - 2 x 3515 (TLM3-FM) - 1 x TLMWH2 (wiring harness)	3539 TLM2X3-KIT - 2 x 3516 (TLM2X3) - 1 x TLMWH2 (wiring harness)	3540 TLM2-KIT - 2 x 3517 (TLM2) - 1 x TLMWH2 (wiring harness)

* The Mojave Series allows you to change up your lens to customize different beam patterns and/or light colors. Remove the lens by removing the bolts around the black bezel (frame around the lens). The lens will then pop right out. A rubber O-ring seals the internal compartment from water and dust. If this is damaged, you can purchase the O-ring separately. Also available are amber lens kits for each light with one replacement O-ring as a backup option. When installing the new lens, make sure the lens sits properly in the alignment groove and is flat against the O-ring. When tightening down the bezel, the best practice is to slowly tighten the bolts across from each other, not in a circle (similar to changing a tire).

Example Add-On Part Photos:



4" Black
Graphic Lens
Cover (3526)



5" O-Ring
Seal (3529)



3" Amber
Lens Pack
(3521)